

The background of the entire image is a dark, monochromatic marbled pattern. It features intricate, swirling veins of light gray and white against a dark charcoal or black base, creating a sophisticated and organic texture.

Nuovo Spazio

Stone Collection

PORCELAIN TILES




Nuovo Spazio

Stone Collection

The clean, airy feeling of this white range makes it a favourite among designers and architects who want minimalist simplicity with warmth and personality. Special pieces like the rough brick mosaic complement the range beautifully by adding texture. With natural, polished or structured finishes, this range can be used indoors or out and is perfect for wet areas such as pools, spas and bathrooms.

1 COLOUR | 4 SIZES | 4 FINISHES



Nuovo Spazio
Nuovo Spazio

Colours

COLOUR	FINISH	SIZE(MM)
Nuovo Spazio	Structured (R10)	600 X 1200 X 12
Nuovo Spazio	Natural (R10)	600 X 1200 X 11
Nuovo Spazio	Structured (R10)	600 X 900 X 11
Nuovo Spazio	Structured (R10)	600 X 600 X 12
Nuovo Spazio	Natural (R10)	600 X 600 X 10
Nuovo Spazio	Polished	600 X 600 X 10
Nuovo Spazio	Structured (R11)	600 X 600 X 10
Nuovo Spazio	Polished	600 X 600
Nuovo Spazio	Structured (R10)	300 X 600 X 12
Nuovo Spazio	Natural (R10)	300 X 600 X 10
Nuovo Spazio	Polished	300 X 600 X 10
Nuovo Spazio	Structured (R11)	300 X 600 X 10


Size Guide (mm)






Nuovo Spazio - Brick Mosaic

Special Pieces



Mosaic



Brick Mosaic



Romanesque

DETAIL	COLOUR	FINISH	SIZE(MM)
Nuovo Spazio	Natural	300 X 600 X 30	Step Tile - Gradone
Nuovo Spazio	Natural	300 X 600 X 30	Step Tile - Gradone Angolare DX
Nuovo Spazio	Natural	300 X 600 X 30	Step Tile - Gradone Angolare SX
Nuovo Spazio	Natural	300 X 600 X 10	Step Tile B+R
Nuovo Spazio	Structured	300 X 600 X 10	Step Tile B+R
Nuovo Spazio	Natural	90 X 600 X 10	Skirting Tile
Nuovo Spazio	Natural	300 X 300 X 10	Mosaic (23x23mm)
Nuovo Spazio	Structured	300 X 300 X 10	Brick Mosaic
Nuovo Spazio	Structured	300 X 300 X 10	Mosaic (23x23mm)




Technical Details

SPECIFICATION	TEST METHODS	REQUIRED VALUE	MANUFACTURERS MEAN VALUES
Length and width	ISO 10545-2	± 0.6%	± 0.2%
Thickness	ISO 10545-2	± 5%	± 5%
Linearity	ISO 10545-2	± 0.5%	± 0.5%
Wedging	ISO 10545-2	± 0.6%	± 0.2%
Warpage	ISO 10545-2	± 0.5%	± 0.2%
Water absorbtion	ISO 10545-3	≤ 0.5%	0.04%
Flexion resistance	ISO 10545-4	≥ 35 N/mm ²	56 N/mm ²
Deep abrasion resistance	ISO 10545-6	Max 175mm ³	128mm ³
Coefficient of linear thermal-expansion	ISO 10545-8	On request	On request
Termal shock resistance	ISO 10545-9	No sample must show visible defects	Resistant
Frost resistance	ISO 10545-12	Must not produce noticeable alteration to surface	Frost-proof
Chemical resistance	ISO 10545-13	Must not produce noticable signs of chemical attack	Resistant
Friction coefficient (slipperiness)	DIN 51130	Test method available	See sizes and specification table

Shade Tone Variance

Shade, texture and tone can vary from piece to piece within a single tile production run. V1 shade tone variation has little or no change from piece to piece where a V4 might have a substantial variety of shade, texture and tone variation.



Variance Rating	Description
V1	Uniform Appearance
V2	Slight Variation
V3	Moderate Variation
V4	Substantial Variation

Colour	Variance
Nuovo Spazio	V2

Ramp Test Values (DIN 51130)

DIN Standard Ramp Testing (DIN 51130) is an alternative to Pendulum Testing and generally categorised as an ‘off-site’ activity because of the size and complexity of the equipment required to carry out the test. The Slip Resistance Values (RSV) are factory gate values (based on supplied tiles) and categorised using the Ramp Test (DIN 51130) method which is commonly used by European factories. In this method, a lubricated inclined platform is adjusted to a gradually increasing gradient, and the angle is measured at which a person walking on it slips.

R Rating Value	Friction
R9	Minimal
R10	Normal
R11	Good
R12	Good
R13	Very High

Colour	Finish/Style	R Rating Value	Friction
Nuovo Spazio	Natural (R10)	R10	Normal
Nuovo Spazio	Structured (R10)	R10	Normal
Nuovo Spazio	Structured (R11)	R11	Good



Environmental Certification



LEED® certification provides independent, third party verification that a building project meets the highest green building and performance measure. All certified projects receive a LEED® plaque, which is nationally recognised symbol demonstrating that a building is environmentally responsible, profitable and a healthy place to live and work. The environmental characteristics have been evaluated and found according to the requirements of content of recycled material for environmental assessment according to LEED® criteria. These products contribute to the increase in the LEED® rating of buildings where they are used.



The EU Ecolabel helps you identify products and services that have a reduced environmental impact throughout their life cycle, from the extraction of raw material through to production, use and disposal. Recognised throughout Europe, EU Ecolabel is a voluntary label promoting environmental excellence which can be trusted. Ecolabel certification applies to building products such as ceramic tiles for residential and public flooring and wall-covering. The commission in charge of the certification system measures the environmental impact caused by the entire productive cycle; in the case of ceramic tiles, the verification starts from raw material quarrying through to manufacturing, distribution, installation and their final disposal. Our factories conform and are certified by the European Community standard Ecolabel and the production process is in complete harmony with the Ecolabel certification.



GREENGUARD Certification ensures that a product meets stringent standards for minimal emissions of volatile organic compounds (VOCs) into indoor air. This program provides assurance that products designed for indoor use adhere to strict chemical emissions limits, fostering the creation of healthier interiors. Manufacturers with GREENGUARD Certification gain credibility for their sustainability claims, supported by empirical technical data from an unbiased third-party organisation. The GREENGUARD Certification Program instills confidence by ensuring that indoor products meet strict chemical emissions limits, contributing to the creation of healthier interior spaces. This empowers manufacturers to produce and customers to identify products with low chemical emissions, thereby supporting air quality and environmental well-being.



NSF® has facilitated the development of more than 75 standards and protocols for sanitary food equipment, and has certified thousands of products as safe to use in restaurant and commercial kitchen settings. NSF® food equipment standards include requirements for material safety, design, construction and product performance. The products conform to the requirements of NSF/ANSI Standard 51 – Food Equipment Materials. NSF/ANSI 51 establishes minimum public health and sanitation requirements for materials and finishes used in the manufacture of commercial foodservice equipment



An Environmental Product Declaration (EPD) is a concise document that transparently communicates the environmental performance of a product throughout its life cycle. It provides comprehensive information about the product's environmental impact, including aspects such as raw material extraction, production processes, energy consumption, and emissions. EPDs are based on standardised methodologies and enable consumers, businesses, and policymakers to make informed decisions by considering the environmental aspects of a product in a systematic and comparable way.

P O R C E L A I N T I L E S

North London Showroom
23 Temple Fortune Parade
Finchley Road
London NW11 0QS
020 3141 3337

www.porcelaintiles.co.uk

South London Showroom
88 High Street Wimbledon
London SW19 5EG
020 3141 3337

enquiry@porcelaintiles.co.uk